



US006696513B1

(12) **United States Patent**
Welton et al.

(10) **Patent No.: US 6,696,513 B1**
(45) **Date of Patent: Feb. 24, 2004**

(54) **CAPSTOCK POLYMER COMPOSITION**

(75) Inventors: **Nicholas Jason Welton**, Solihull (GB);
Keith Herbert Dodd, Richmond Park
(GB)

(73) Assignee: **H. B. Fuller Coatings Ltd.**,
Birmingham (GB)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/868,831**

(22) PCT Filed: **Dec. 22, 1999**

(86) PCT No.: **PCT/GB99/04353**

§ 371 (c)(1),
(2), (4) Date: **Nov. 29, 2001**

(87) PCT Pub. No.: **WO00/37557**

PCT Pub. Date: **Jun. 29, 2000**

(30) **Foreign Application Priority Data**

Dec. 22, 1998 (EP) 98310616

(51) **Int. Cl.⁷** **C08K 3/10**

(52) **U.S. Cl.** **524/405; 524/409; 524/432**

(58) **Field of Search** **524/405, 404,**
524/409, 432

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,032,498 A * 6/1977 Dany et al. 260/30.6 R

4,129,535 A * 12/1978 Elcik 260/23 XA
4,965,309 A * 10/1990 Batdorf 524/405
5,200,446 A * 4/1993 Bergner 524/173
5,322,899 A * 6/1994 Grunewalder et al. 525/199

OTHER PUBLICATIONS

Arakawa, K., et al., "Effect of Flame Retardant Elements on
Combustibility of Poly (methyl methacrylate)", *Kobunshi*
Ronbunshu (Collected Polymer Articles), vol. 30, No. 10,
pp. 643-647 (Oct. 1974).

Derwent Publications Ltd. World Patent Index (WPI)
abstract of Japanese Patent Publication No. 54034359, 1979.

Razinskaya, I.N., et al., "Investigation of Synergism of
Fireproofing Compounds in Compositions Based on PMMA
Using Design of Experiments", *Plast Massy*, No. 2, pp.
49-50 (1983).

International Search Report for International Application
No. PCT/GB 99/04353, mailed Jun. 15, 2000.

* cited by examiner

Primary Examiner—James J. Seidleck

Assistant Examiner—U. K. Rajguru

(74) *Attorney, Agent, or Firm*—Senniger, Powers, Leavitt
& Roedel

(57) **ABSTRACT**

The invention relates to a capstock polymer composition
comprising a blend of a melt extrudable acrylic polymer
component; from 10% to 50% by weight of a halogen donor
component; a halogen volatilisation component; and a char-
inducing component which induces formation of a char upon
application of flame to the composition.

9 Claims, No Drawings